

<b>1. IDENTIFICATION OF THE SUBSTANCE AND THE COMPANY UNDERTAKING</b>
---

**1.1 Product identifier**

Product name                      Solu-Cal S Enhanced Gypsum #12020

**1.2 Relevant use of the product**

Applications                      Fertilizers

**1.3 Manufacturer, Importer or Responsible Party**

Name                                FERTI TECHNOLOGIES  
 Address                            560, Chemin Rhéaume, C.P 129  
    JOL 2J0  
    Saint-Michel, Québec, Canada  
 Telephone                        450 454-7521  
 Contact email                    astpierre@fertitechno.com

**1.4 Emergency phone number**

Telephone                        USA National Capital Poison Center: 1 800 222 1222

<b>2. HAZARDS IDENTIFICATION</b>
----------------------------------

**2.1. The hazard classification of the chemical according to HCS 2012 (US-GHS)**

Carc. 1A	H350
STOT SE 3	H335
STOT RE 2	H372

**2.2. Danger symbols**



**2.3. Signal word**

Danger

**2.4. Hazard statements**

H350 May cause cancer.  
 H335 May cause respiratory irritation  
 H372 May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

**2.5. Precautionary statements**

Prevention                        P201 Obtain special instructions before use.

Response	<p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P260 Do not breathe dust.</p> <p>P264 Wash hands thoroughly after handling.</p> <p>P270 Do not eat, drink or smoke when using this product.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.</p> <p>P330 Rinse mouth.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P314 Get medical advice/attention if you feel unwell.</p>
Storage	P405 Store locked up.
Disposal	P501 Dispose of contents/container according to local regulations.

- 2.6. **Description of any hazards not otherwise classified** Not applicable.
- 2.7. **% ingredient(s) with unknown acute toxicity** Not applicable.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

	Chemical name	CAS-Nr.	Concentration %
Gypsum mix	Gypsum	1317-65-3	C => 95%
	Crystalline silica	14808-60-7	C = 0.1- 1%
	Humic acid	n/a	C = <1%

**4. FIRST AID MEASURES**

**4.1 First Aid measures after Inhalation**

Following inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided by a qualified operator. Get medical attention if irritation develops and persists.

**4.2 First Aid measures after Skin exposure**

Following skin contact      Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Get medical attention if irritation develops and persists.

**4.3 First Aid measures after Eye exposure**

Following eye contact      Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

**4.4 First Aid measures after Ingestion**

Following ingestion      Induce vomiting, but only if victim is fully conscious. Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Do not give milk or alcoholic beverages. Call a physician.

**4.5 Most important symptoms and effects, both acute and delayed**

INHALATION	May cause respiratory irritation.
SKIN	None known.
EYES	Dust can cause temporary mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult a physician.
INGESTION	None known

**4.6 Indication of any immediate medical attention and special treatment needed**

Notes to physician:      Treat symptomatically.

**5. FIREFIGHTING MEASURES**

**5.1 Extinguishing media**

Suitable:  
 Use extinguishing agent suitable for type of surrounding fire. Avoid excessive water to minimize runoff. Prevent firefighter water from entering the environment.  
 Small fires: Water spray, foam, dry chemical or CO2  
 Large fires: Water spray, fog or foam.

Unsuitable: Not applicable.

**5.2 Special hazards arising from chemical or mixture during the fire**

Container may rupture on heating. Cool closed containers exposed to fire with water spray. Do not allow run-off from firefighting to enter drains or water courses. Explosive reactions with oxidizing agents such as potassium chlorate and/or peroxides. In case of fire hazardous decomposition products may be produced such as:

- Ammonia
- Carbon monoxide
- Carbon dioxide (CO2)

**5.3 Special Protective Precautions or equipment for firefighters**

In the event of fire and/or explosion do not breathe fumes. In the case of respirable dust and/or fumes, use self-contained breathing apparatus and dust impervious protective suit.

**6. ACCIDENTAL RELEASE MEASURES**

- 6.1 Personal precautions, protective equipment**      Wear personal protective equipment.
- 6.2 Emergency procedures**      Unprotected persons must be kept away.  
Evacuate personnel to safe areas.  
Provide adequate ventilation.  
Avoid dust formation.  
Avoid breathing dust.  
Avoid contact with skin, eyes and clothing.
- 6.3 Methods and materials used for containment**      Do not flush into surface water or sanitary sewer system.  
Prevent further leakage or spillage if safe to do so.  
Do not let product enter drains.
- 6.4 Clean-up procedures**      Use mechanical handling equipment.  
Clean contaminated surface thoroughly.  
Pick up and arrange disposal without creating dust.  
Use a suitable vacuum cleaner.

**7. HANDLING AND STORAGE**

- 7.1 Precautions for safe handling**      Handle with care.  
Wear personal protective equipment.  
Use only in well-ventilated areas.  
Avoid dust formation.  
Provide exhaust ventilation if dust is formed.  
Dust must be extracted directly at the point of origin.  
Avoid breathing dust.  
Avoid contact with skin, eyes and clothing.
- 7.2 Conditions for safe storage**      Keep containers tightly closed in a dry, cool and well-ventilated place.  
Containers should be protected against falling down.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store away from incompatible substances.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 ACGIH-Threshold Limit Value (TLV)**

Exposure limit values of the components: Respirable crystalline silica dust: ACGIH TLV® = 0,05 mg/m<sup>3</sup>

**8.2 OSHA-Permissible Exposure Limit (PEL)**

Exposure limit values of the components:

Component / CAS	TLV, 8H (OSHA, PEL, ACGIH)
	mg/m <sup>3</sup>
Quartz (SiO <sub>2</sub> ) CAS N°: 14808-60-7	Total dust: 30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 (OSHA Z-3) Respirable: 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 (OSHA Z-3) Respirable: 250 mppcf / %SiO <sub>2</sub> +5 (OSHA Z-3)

Gypsum CAS N°: 1317-65-3	Total dust: 15 mg/m <sup>3</sup> (OSHA Z-1) Respirable: 5 mg/m <sup>3</sup> (OSHA Z-1)
-----------------------------	---

**8.3 Any other exposure limit used or recommended by chemical manufacturer**

Non applicable

**8.4 Engineering Controls**

Provide exhaust ventilation if dust is formed. Dust must be extracted directly at the point of origin. Apply technical measures to comply with the occupational exposure limits.

**8.5 Personal Protective Equipment**

Hand protection: Gloves

Gloves must be inspected prior to use. Replace when worn.

Eye protection: Do not wear contact lenses.

Wear as appropriate: Safety glasses with side-shields

Body protection: Long sleeved clothing

Respiratory protection: A NIOSH approved air purifying respirator with a type 95 (R or P) particulate filter may be used under conditions where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed if workplace conditions warrant a respirator use.

Hygiene measures: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use. Keep working clothes separately.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information of basic physical and chemical properties**

Appearance (physical state, colour, etc.)	White to off white
Odour	Low to no odour
Odour threshold	Not applicable
pH	No data available
Melting point/freezing point;	No data available
Boiling point	Not applicable
Boiling Range	Not applicable

Flash point	No data available
Evaporation rate	Not applicable
Flammability	Not flammable
Upper/lower flammability or explosive limits	No data available
Oxidising properties	No data available
Vapour pressure	Not applicable
Vapour density	No data available
Density	No data available
Solubility in water	Partially soluble
Other Solvents	No data available
Partition coefficient (n-octanol/water)	No data available
Auto ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Not applicable

## 10. STABILITY AND REACTIVITY

<b>10.1 Reactivity</b>	Contains Limestone which reacts with acids. It forms carbon dioxide (CO <sub>2</sub> ). This displaces the oxygen in the air in closed spaces. (danger of suffocation)
<b>10.2 Chemical stability</b>	Stable under recommended storage conditions.
<b>10.3 Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>10.4 Conditions to avoid</b>	Contact with incompatible materials
<b>10.5 Incompatible materials</b>	None known.
<b>10.6 Hazardous decomposition products</b>	Gypsum ignites on contact with fluorine and is incompatible with acids, ammonium salts and magnesium.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Measures of Toxicity

Acute toxicity:

Gypsum:

Acute toxicity: LD50 Oral (Rat): > 5,000 mg/kg

Silica:

Acute toxicity: LD50 (Rat): 5,000 mg/kg

(Mouse): >15000 mg/Kg

Skin corrosion/irritation:

No data available

Serious eye damage/irritation:

No data available

Respiratory or skin sensitisation:

Product:

no data available

**11.2 Listed in IARC or considered carcinogen by NTP or OSHA**

Quartz (SiO<sub>2</sub>)

CAS N°: 14808-60-7

Group 1 (IARC), Volume 68, 100C

**11.3 Further information**

This product contains prismatic tremolite (e.g., cleavage fragments) as an impurity. Sufficient exposure to respirable prismatic tremolite dust may cause serious lung problems.

## 12. ECOLOGICAL INFORMATION

**12.1 Toxicity**

Ingredients:

Silica (quartz):

Toxicity to fish :

LC50: > 10,000 mg/l

Exposure time: 96 h

Species: *Oncorhynchus mykiss* (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates:

EC50: >1000mg/l (Exposure time:48 h)

Species: *Daphnia magna* (Water flea)

EC50: 200 mg/l (Exposure time:72h)

Species: *Desmodesmus subspicatus* (green algae)

Gypsum:

This product has no known effect on ecology. Toxicity studies of gypsum performed with fish, aquatic invertebrates and aquatic plants showed no toxic effects.

**12.2 Persistence and degradability**

No data available



# SAFETY DATA SHEET

## Solu-Cal S Enhanced Gypsum #12020

Version 1.0  
Version Date  
10/26/2015

<b>12.3 Bioaccumulative potential</b>	No data available
<b>12.4 Mobility in soil</b>	No data available
<b>12.5 Other adverse effects</b>	May release ammonium ions that are toxic to fish. Un-ionized ammonia concentrations above 0.02 mg/l are considered toxic in fresh water. May release phosphates which will result in algae growth, increased turbidity, and depleted oxygen. At extremely high concentrations, this may be hazardous to fish or other marine organisms. Release to watercourses may cause effects downstream. Fish 96 hour LC50, OECD Guidelines 203 (rainbow trout): >86mg/L.

### 13. DISPOSAL CONSIDERATIONS

<b>13.1 Disposal methods to employ</b>	Recover or recycle if possible. Properly characterize all waste materials. Consult federal, state/provincial and local regulations regarding the proper disposal of this material. Prevent material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>13.2 Description of appropriate disposal containers to use</b>	No data available
<b>13.3 Description of the physical and chemical properties that may affect disposal activities</b>	No data available
<b>13.4 Language discouraging sewage disposal.</b>	No data available
<b>13.5 Any special precautions for landfills or incineration activities</b>	No data available

### 14. TRANSPORT INFORMATION

UN Number .....  
UN proper shipping name .....





**SAFETY DATA SHEET**  
**Solu-Cal S Enhanced Gypsum #12020**

Version 1.0  
 Version Date  
 10/26/2015

**Transport hazard classes** .....

**Packing group** .....

**Environmental hazards** .....

**Guidance On transport in bulk** .....

**Special precautions for user** .....

**15. REGULATORY INFORMATION**

**National and/or regional regulatory information of the chemical or mixtures**

Inventories:

US. Toxic Substances Control Act: No data available

OSHA Hazards: Carcinogen

Clean Air Act: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

**16. OTHER INFORMATION**

**Indications on the revision**

First edition: 08/10/2015

Addition of all fields as required by regulation (US) HCS 1910.1200 [HCS 2012].

Update of the classification information and update of related sections accordingly.

**Abbreviations and acronyms used**

ACGIH: American conference of governmental and industrial hygienist

CAS N°.: Chemical Abstract Service Number

CFR: Code of Federal Regulations

EC50: Half maximal effective concentration

IARC: International agency for the research on cancer

IC50: Half maximal inhibitory concentration

HCS: Hazard communication standard

NIOSH: National institute of occupational safety and health

LC50: Half maximal lethal concentration

LD50: Half maximal lethal dose

OSHA: Occupational safety and health administration

STOT SE: Specific target organ toxicity Single exposure

UN N°.: United Nations Number



**SAFETY DATA SHEET**  
**Solu-Cal S Enhanced Gypsum #12020**

Version 1.0  
Version Date  
10/26/2015

**Methods of evaluation for the classification of mixtures**

The classification of the mixture was set based on the regulation (US) HCS 1910.1200 [HCS 2012].

**Other information**

This information is based on our present knowledge and is provided according to the relevant national regulations. This information is intended as a characterization of the product in order to provide guidance for the relevant safety issues. However, this document does not provide any warranty, expressed or implied, regarding the properties of the product.